

## FIELD MOUNTED PROCESS INDICATOR WITH DUAL RELAYS

8080RR

- 4 TO 20 mA INPUT
- 4 DIGIT LED DISPLAY IN ENGINEERING UNITS
- CHOICE OF COPPER-FREE ALUMINUM OR SS316 ENCLOSURE
- TWO INDEPENDENT USER ASSIGNABLE ALARMS
- EXPLOSION PROOF CERTIFIED
- OUTPUT 4 TO 20 Ma (Retransmission)
- 3 YEAR WARRANTY



### Introduction

IME Model 8080RR Digital Indicator allows the process variable from any transmitter to be monitored in engineering units and two corresponding alarms to be assigned. Both alarms can be assigned either high or low within the selected range. In addition to that the unit also provides 4 to 20 mA output.

### Description

IME Model 8080RR Indicators are designed for use in process industries where vibration, inclement weather and corrosive atmospheres prevail. The electronics are enclosed in a copper-free epoxy coated Aluminum housing and for more aggressive environments, a SS316 housing is optionally available. The housings meet the requirements of NEMA 4X & IP68, and are also certified Explosion Proof by FM/CSA/ATEX/IECEX.

### LED Meter

The Model 8080RR has 4 digit display and can be configured to read from -999 to 9999 with a 4-20 mA input signal. The decimal point location, engineering units, alarm settings, etc can be adjusted using membrane key on the front panel.

### Mounting

The Model 8080RR can be wall mounted or mounted on a 2" pipe. For mounting the unit on a wall or 2" pipe, a wide choice of stainless steel mounting brackets are also available.

### Certification System

	CLASS I, DIV I GROUPS B, C AND D CLASS II/III, DIV I GROUPS E, F AND G NEMA 4X, T6	
	CLASS I, DIV I GROUPS B, C AND D CLASS II/III, DIV I GROUPS E, F AND G NEMA 4X, T6	
	II 2G D Ex d IIC T6 Gb Ex tb IIIC T85°C Db IP68 Ta = -40°C to +60°C	
	Ex d IIC T6 Gb Ex tb IIIC T85°C Db IP68 Ta = -40°C to +60°C	

### Functional Specifications

#### Indication Accuracy

0.1% of calibrated range  $\pm 1$  digit

#### Set Point Adjustment

10~100% of full scale, user selectable

#### Reset

Automatically when the input falls below the alarm set point by approximately  $\pm 0.5\%$  of full scale.

#### Alarm Set Point Accuracy

$\pm 0.5\%$  of full scale.

#### Alarm Status Indication

LED on front panel

#### Display Height

10mm (0.4") high

#### Alarm Output

2 sets SPDT, 1 form C, rated 10A @ 250V AC, 50/60Hz

#### Stability Over Time

0.1% of calibrated range  $\pm 1$  digit over 6 months

#### Over Range Indication

Flashing of display

#### Response Time

Typically 75ms

#### Supply Voltage

18~28V DC

#### Operating Temperature

-40°C to +60°C

#### Weight

0.9Kg (2 lbs) for Aluminum Unit and 1.4Kg (3 lbs) for SS316 Unit

#### Material of Construction of Enclosure

Epoxy coated Copper-Free Aluminum or SS316 as specified

#### O Rings

Buna N (Nitrile)

#### Optional Accessories


Mounting Brackets (Model 175PM, 175RC, 175NR, 175MM)

## ORDERING INFORMATION FOR 8080RR

Model	Description																																																			
8080RR	Field Mounted Process Indicator With Dual Relays																																																			
	<table border="1"> <thead> <tr> <th>Code</th> <th>Options, Housing</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>Die cast Aluminum, Epoxy Coated</td> </tr> <tr> <td>T</td> <td>SS316, Electro Polished</td> </tr> </tbody> </table>	Code	Options, Housing	A	Die cast Aluminum, Epoxy Coated	T	SS316, Electro Polished																																													
Code	Options, Housing																																																			
A	Die cast Aluminum, Epoxy Coated																																																			
T	SS316, Electro Polished																																																			
	<table border="1"> <thead> <tr> <th>Code</th> <th>Instrument Connection (T1)</th> <th>Conduit Size (T2)</th> </tr> </thead> <tbody> <tr><td>01</td><td>M16 x 2P (See note 1)</td><td>3/4" NPT</td></tr> <tr><td>02</td><td>M16 x 2P (See note 1)</td><td>1/2" NPT</td></tr> <tr><td>03</td><td>M16 x 2P (See note 1)</td><td>M20 x 1.5P</td></tr> <tr><td>04</td><td>1/2" NPT</td><td>3/4" NPT</td></tr> <tr><td>05</td><td>1/2" NPT</td><td>1/2" NPT</td></tr> <tr><td>06</td><td>1/2" NPT</td><td>M20 x 1.5P</td></tr> <tr><td>07</td><td>3/4" NPT</td><td>3/4" NPT</td></tr> <tr><td>08</td><td>3/4" NPT</td><td>1/2" NPT</td></tr> <tr><td>09</td><td>3/4" NPT</td><td>M20 x 1.5P</td></tr> <tr><td>10</td><td>1/2" BSP</td><td>3/4" NPT</td></tr> <tr><td>11</td><td>1/2" BSP</td><td>1/2" NPT</td></tr> <tr><td>12</td><td>1/2" BSP</td><td>M20 x 1.5P</td></tr> <tr><td>13</td><td>3/4" NPT</td><td>None</td></tr> <tr><td>14</td><td>M20 x 1.5P</td><td>None</td></tr> <tr><td>16</td><td>1/2" BSP</td><td>None</td></tr> <tr><td>17</td><td>1/2" NPT</td><td>None</td></tr> </tbody> </table>	Code	Instrument Connection (T1)	Conduit Size (T2)	01	M16 x 2P (See note 1)	3/4" NPT	02	M16 x 2P (See note 1)	1/2" NPT	03	M16 x 2P (See note 1)	M20 x 1.5P	04	1/2" NPT	3/4" NPT	05	1/2" NPT	1/2" NPT	06	1/2" NPT	M20 x 1.5P	07	3/4" NPT	3/4" NPT	08	3/4" NPT	1/2" NPT	09	3/4" NPT	M20 x 1.5P	10	1/2" BSP	3/4" NPT	11	1/2" BSP	1/2" NPT	12	1/2" BSP	M20 x 1.5P	13	3/4" NPT	None	14	M20 x 1.5P	None	16	1/2" BSP	None	17	1/2" NPT	None
Code	Instrument Connection (T1)	Conduit Size (T2)																																																		
01	M16 x 2P (See note 1)	3/4" NPT																																																		
02	M16 x 2P (See note 1)	1/2" NPT																																																		
03	M16 x 2P (See note 1)	M20 x 1.5P																																																		
04	1/2" NPT	3/4" NPT																																																		
05	1/2" NPT	1/2" NPT																																																		
06	1/2" NPT	M20 x 1.5P																																																		
07	3/4" NPT	3/4" NPT																																																		
08	3/4" NPT	1/2" NPT																																																		
09	3/4" NPT	M20 x 1.5P																																																		
10	1/2" BSP	3/4" NPT																																																		
11	1/2" BSP	1/2" NPT																																																		
12	1/2" BSP	M20 x 1.5P																																																		
13	3/4" NPT	None																																																		
14	M20 x 1.5P	None																																																		
16	1/2" BSP	None																																																		
17	1/2" NPT	None																																																		
	<table border="1"> <thead> <tr> <th>Code</th> <th>Certification</th> </tr> </thead> <tbody> <tr> <td>NN</td> <td>None</td> </tr> <tr> <td>E1</td> <td>FM / CSA / ATEX / IECEx Explosion Proof Certified, NEMA 4X, IP68, T6</td> </tr> </tbody> </table>	Code	Certification	NN	None	E1	FM / CSA / ATEX / IECEx Explosion Proof Certified, NEMA 4X, IP68, T6																																													
Code	Certification																																																			
NN	None																																																			
E1	FM / CSA / ATEX / IECEx Explosion Proof Certified, NEMA 4X, IP68, T6																																																			
	<table border="1"> <thead> <tr> <th>Code</th> <th>Accessories</th> </tr> </thead> <tbody> <tr> <td>RC</td> <td>Model 175RC Mounting Bracket (See note 1)</td> </tr> <tr> <td>PM</td> <td>Model 175PM Mounting Bracket (See note 1)</td> </tr> <tr> <td>NR</td> <td>Model 175NR Mounting Bracket</td> </tr> <tr> <td>MM</td> <td>Model 175MM Mounting Bracket</td> </tr> </tbody> </table>	Code	Accessories	RC	Model 175RC Mounting Bracket (See note 1)	PM	Model 175PM Mounting Bracket (See note 1)	NR	Model 175NR Mounting Bracket	MM	Model 175MM Mounting Bracket																																									
Code	Accessories																																																			
RC	Model 175RC Mounting Bracket (See note 1)																																																			
PM	Model 175PM Mounting Bracket (See note 1)																																																			
NR	Model 175NR Mounting Bracket																																																			
MM	Model 175MM Mounting Bracket																																																			
	<table border="1"> <thead> <tr> <th>Code</th> <th>2 Inch "U" Bolt with Nuts and Washers</th> </tr> </thead> <tbody> <tr> <td>00</td> <td>None</td> </tr> <tr> <td>01</td> <td>Model 17508, 1 Set (For Model 175RC)</td> </tr> <tr> <td>02</td> <td>Model 17508, 2 Sets (For Model 175PM &amp; 175NR)</td> </tr> </tbody> </table>	Code	2 Inch "U" Bolt with Nuts and Washers	00	None	01	Model 17508, 1 Set (For Model 175RC)	02	Model 17508, 2 Sets (For Model 175PM & 175NR)																																											
Code	2 Inch "U" Bolt with Nuts and Washers																																																			
00	None																																																			
01	Model 17508, 1 Set (For Model 175RC)																																																			
02	Model 17508, 2 Sets (For Model 175PM & 175NR)																																																			
8080RR	A 01 E1 RC 02 ← Typical Model Number																																																			

Note:


- 1 Ports with M16 x 2P thread are not through holes, they are for use with Model 175RC and 175PM Mounting Brackets only.




## MOUNTING BRACKETS FOR INDICATORS AND TRANSMITTERS

### Mounting Methods For Model 175RC

#### Pipe Mounting




#### Wall / Panel Mounting




### Mounting Methods For Model 175PM

#### Pipe Mounting




#### Wall / Panel Mounting



## MOUNTING BRACKETS FOR INDICATORS AND TRANSMITTERS


### Mounting Methods For Model 175NR

#### Pipe Mounting



### Mounting Methods For Model 175MM

#### Wall/Panel Mounting



## Mounting Bracket


175RC

### Introduction

This simple hollow square mounting bracket constructed out of SS316 Stainless Steel, can be used to mount a variety of field devices, either on a wall or panel or a 2" Pipe.

When mounting on a 2" pipe, a "U" Bolt is required, which can be supplied optionally.

IME Model 17508 consists of a complete assembly of a 2" U bolt along with the nuts and washers required.



## Mounting Bracket


175PM

### Introduction

This simple "L" Shape mounting bracket constructed out of SS316 Stainless Steel, can be used to mount a variety of field devices, either on a wall or panel or on a 2" pipe.

When mounting on a 2" pipe, a "U" Bolt is required, which can be supplied optionally.

IME Model 17508 consists of a complete assembly of a 2" U bolt along with the nuts and washers required.



## Mounting Bracket


175NR

### Introduction

IME MODEL 175NR is Stainless Steel Mounting Brackets made exclusively for IME MODEL 8080 Instrument Enclosure to mount on a 2" Pipe.

This Bracket is available for customers who require all 3 ports on the enclosure for other purposes.

The 175NR is symmetrical, so it can be rotated 90° to suit the viewing position of the Indicator/Transmitter.



## Mounting Bracket

175MM

### Introduction

IME MODEL 175MM is Stainless Steel Mounting Brackets made exclusively for IME MODEL 8080 Instrument Enclosure to mount on wall.

This low cost Bracket is available for customers who require all 3 ports on the enclosure for other purposes.

